

## **RULE BREAKER STRIPE TILE QA135**

## PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Rule Breaker Stripe Tile / QA135
PRODUCT TYPE	Carpet Tile
FIBER TYPE	EnviroStrand SD PET
BACKING	UltraSet Matrix
CONSTRUCTION	Tufted
SURFACE APPEARANCE	Patterned Loop
DYE METHOD	Solution Dyed
INSTALLATION METHODS	QuarterTurn, BrickAshlar
SIZE	24" x 24" (.6096 m x .6096 m)
GAUGE	1/10 (39.37 rows per 10 cm)
STITCHES PER INCH	10.2 (40.16 per 10cm)
STAIN RELEASE TECHNOLOGY	Mohawk Protection Plus Stain
DENSITY	7,098
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS	Green Label Plus
SOIL RELEASE TECHNOLOGY	Mohawk Protection Plus Soil
TUFTED WEIGHT	14 oz. per sq. yd. (474 g/m2)
WARRANTIES	10 Year Limited Wear Warranty 10 Year Limited Static Protection Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Edge Ravel, Zippering, Delaminationand Dimensional Stability Warranty