

ROOTED AH008

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Rooted / AH008
PRODUCT TYPE	LVT
COLLECTION NAME	SolidTech
CONSTRUCTION	Rigid Composite Core LVT
WEAR LAYER THICKNESS	12 mil (0.3mm)
INSTALLATION METHOD	Floating
GAUGE	6.5 mm (with pad)
SIZE	7" x 49"
FINISH	Enhanced Urethane
FLEXIBILITY	ASTM F137 - Passes - 1 in. Mandrel / No crack or break
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 6hrs @ 180°F, 0.12%
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8%
SLIP RESISTANCE	ASTM D2047 - Passes - > 0.6
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No Change or Slight Change
RESISTANCE TO LIGHT	ASTM F1515 - Passes - ΔF < 8
RESISTANCE TO HEAT	ASTM F1514 - Passes - ΔF < 8
CRITICAL RADIANT FLUX	ASTM E648 - Passes - > .45 watts/cm ² , Class 1
SMOKE DENSITY	ASTM E662 - Passes
OPTIONAL UNDERLAYMENT	N/A
CERTIFICATION	FloorScore® Certified
DESCRIPTION	Aladdin Commercial's SolidTech Collection brings fashion-forward design with innovative performance and technology. Featuring an array of colorways and textures, SolidTech's random plank variation and larger pattern repeats ensure beautiful natural looking floors.
INSTALLATION	Floating
WARRANTIES	Limited 10 Year Light Commercial Warranty Limited 35 Year Residential Warranty