

## BARRALI AH011

### PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Barrali / AH011
PRODUCT TYPE	LVT
CONSTRUCTION	Luxury Vinyl Tile
WEAR LAYER THICKNESS	20 mil (0.5mm)
INSTALLATION METHOD	GlueDown
GAUGE	2.5 mm
FINISH	M-Force 1™ Enhanced Urethane
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
FLEXIBILITY	ASTM F137 - Passes - 1" Mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8%, maximum single reading 10%
SLIP RESISTANCE	ASTM C1028 - Passes - Wet: greater than / equal to 0.5
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dulling, surface attack, or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM F1514 - Passes - $\Delta F < 8$
CRITICAL RADIANT FLUX	ASTM E648 - Class 1 ( $>0.45 \text{ W/cm}^2$ )
SMOKE DENSITY	ASTM E662 Part A - Less than 450
OPTIONAL UNDERLAYMENT	Mohawk AccuSound™
CERTIFICATION	FloorScore® Certified
DESCRIPTION	Featuring a wider plank design and unique visuals from textile to natural wood, Barrali from Aladdin Commercial offers performance LVT fit for a variety of commercial environments.
INSTALLATION	Glue Down
WARRANTIES	Limited 10 Year Commercial Warranty Limited 25 Year Residential Warranty