

GRASS VALLEY 20 AH016

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Grass Valley 20 / AH016
PRODUCT TYPE	LVT
COLLECTION NAME	Grass Valley
CONSTRUCTION	Luxury Vinyl Tile
WEAR LAYER THICKNESS	20 mil (0.5mm)
INSTALLATION METHOD	GlueDown
GAUGE	2.5 mm
SIZE	8" x 48"
FINISH	M-Force™ 1 Enhanced Urethane
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
FLEXIBILITY	ASTM F137 - Passes - 1" Mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8%, maximum single reading 10%
SLIP RESISTANCE	ASTM C1028 - Passes - Wet: greater than/equal to 0.5
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dulling, surface attack, or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM F1514 - Passes - $\Delta E < 8$
CRITICAL RADIANT FLUX	ASTM E648 - Class 1 (>0.45 W/cm ²)
SMOKE DENSITY	ASTM E662 Part A - Less than 450
OPTIONAL UNDERLAYMENT	Mohawk AccuSound™
CERTIFICATION	FloorScore® Certified
DESCRIPTION	Redefining the norm of mixing different materials and styles, Grass Valley offers 11 types of wood mixed with 3 stones. Created with deconstructivism in mind, this collection offers freedom of form and endless opportunities for unique artistic expression.
INSTALLATION	Glue Down
WARRANTIES	Limited 10 Year Light Commercial Warranty Limited 25 Year Residential Warranty