

SOHANA II 12 MIL AH032

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Sohana II 12 mil / AH032
PRODUCT TYPE	LVT
COLLECTION NAME	Sohana
CONSTRUCTION	Luxury Vinyl Tile
WEAR LAYER THICKNESS	12mil (0.30 mm)
INSTALLATION METHOD	GlueDown
GAUGE	2 mm
SIZE	6" x 48"
FINISH	Commercial Urethane Finish
CLASSIFICATION	ASTM F1700-Class III Type A-Smooth, Type B-Embossed
FLEXIBILITY	ASTM F137 - Passes - 1" mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8%
SLIP RESISTANCE	ASTM C1028 - Passes - Wet: greater than / equal to 0.5
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dulling, surface attack, or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM E649 - Class 1 ($> 0.45 \text{ W/cm}^2$)
SMOKE DENSITY	ASTM E662 Part A - Less than 450
CERTIFICATION	FloorScore® Certified
DESCRIPTION	Offering sophistication with a modern-rustic twist, Sohana was inspired by nature-influenced artwork and hues. The wide array of colors and styles allows for easy coordination in a multitude of aesthetics.
INSTALLATION	Glue Down
WARRANTIES	Limited 10 Year Commercial Warranty Limited 25 Year Residential Warranty