

TO TICH STREET AH085

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	To Tich Street / AH085
PRODUCT TYPE	LVT
COLLECTION NAME	Old Quarter
CONSTRUCTION	Luxury Vinyl Tile
WEAR LAYER THICKNESS	12 mil (0.3mm)
INSTALLATION METHOD	Click
GAUGE	4.5mm
SIZE	6" x 48"
FINISH	Enhanced Urethane Finish
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
FLEXIBILITY	ASTM F137 - Passes - 1" mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM E649 - Class 1 ($> 0.45 \text{ W/cm}^2$)
SMOKE DENSITY	ASTM E662 Part A - Less than 450
OPTIONAL UNDERLAYMENT	Mohawk AccuSound™ - Loose lay - Active Sound-Click
CERTIFICATION	FloorScore® Certified
INSTALLATION	Click
WARRANTIES	Limited 6 Year Light Commercial Warranty Limited 25 Year Residential Warranty