

## THUNG STREET AH086

### PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Thung Street / AH086
PRODUCT TYPE	LVT
COLLECTION NAME	Old Quarter
CONSTRUCTION	Luxury Vinyl Tile
WEAR LAYER THICKNESS	20 mil (0.5mm)
INSTALLATION METHOD	Click
GAUGE	5mm
FINISH	Enhanced Urethane Finish
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
FLEXIBILITY	ASTM F137 - Passes - 1" mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 14$
RESISTANCE TO HEAT	ASTM E649 - Class 1 ( $> 0.45$ W/cm <sup>2</sup> )
SMOKE DENSITY	ASTM E662 Part A - Less than 456
OPTIONAL UNDERLAYMENT	Mohawk AccuSound™ - Loose lay - Active Sound-Click
CERTIFICATION	FloorScore® Certified
INSTALLATION	Click
WARRANTIES	Limited 10 Year Light Commercial Warranty Limited Lifetime Residential Warranty